



Golden Century Technology Co., Ltd

Address: No18, Qinghe Anningzhuang Dong Road,
Haidian district, Beijing, China 100085

T/F: +86(0)10 88507752 E: info@gd-flex.com W: www.gd-flex.com


PRODUCTS CATEGORY

Flexible Corrugated Stainless Steel Tube						
Type	Part No.	Flex SS Tube SIZE		Container Volume(meter)		Picture
		OD	ID	20ft	40ft	
DN12	GDSSCSST16025	16mm	12mm	41700	83400	
DN16	GDSSCSST20025	20mm	16mm	24780	49560	
DN20	GDSSCSST25030	25mm	20mm	16560	33120	
DN25	GDSSCSST32030	32mm	26mm	8760	17520	
EPDM Pre Insulated Twin pipe HT ^① System With Jacketing & Sensor Cable						
Type	Part No.	Flex SS Tube SIZE(OD*ID)	HT insulation pipe(Wall mm)	Container Volume(meter)		Picture
				20ft	40ft	
DN12	GDTWHTCSST16025.13	16mm*12mm	13mm	3600	7200	
DN12	GDTWHTCSST16025.20	16mm*12mm	20mm	2200	4400	
DN16	GDTWHTCSST20025.13	20mm*16mm	13mm	3450	6900	
DN16	GDTWHTCSST20025.20	20mm*16mm	20mm	2140	4280	
DN20	GDTWHTCSST25030.13	25mm*20mm	13mm	3450	6900	
DN20	GDTWHTCSST25030.20	25mm*20mm	20mm	1920	3840	
DN25	GDTWHTCSST32030.13	32mm*26mm	13mm	2140	4280	
DN25	GDTWHTCSST32030.20	32mm*26mm	20mm	1200	2400	

Jacketing^② EPDM Pre insulated Single pipe HT System

Type	Part No.	Flex SS Tube SIZE(OD*ID)	HT insulation pipe(Wall mm)	Container Volume(meter)		Picture
				20ft	40ft	
DN12	GDSIHCSST16025J.13	16mm*12mm	13mm	7200	14400	
DN12	GDSIHCSST16025J.20	16mm*12mm	20mm	4400	8800	
DN16	GDSIHCSST20025J.13	20mm*16mm	13mm	6900	13800	
DN16	GDSIHCSST20025J.20	20mm*16mm	20mm	4280	8560	
DN20	GDSIHCSST25030J.13	25mm*20mm	13mm	6900	13800	
DN20	GDSIHCSST25030J.20	25mm*20mm	20mm	3840	7680	
DN25	GDSIHCSST32030J.13	32mm*26mm	13mm	4280	8560	
DN25	GDSIHCSST32030J.20	32mm*26mm	20mm	2400	4800	

Jacketing EPDM Pre insulated Single pipe HT System With Sensor Cable

Type	Part No.	Flex SS Tube SIZE(OD*ID)	HT insulation pipe(Wall mm)	Container Volume(meter)		Picture
				20ft	40ft	
DN12	GDSIHCSST16025JS.13	16mm*12mm	13mm	7200	14400	
DN12	GDSIHCSST16025JS.20	16mm*12mm	20mm	4400	8800	
DN16	GDSIHCSST20025JS.13	20mm*16mm	13mm	6900	13800	
DN16	GDSIHCSST20025JS.20	20mm*16mm	20mm	4280	8560	
DN20	GDSIHCSST25030JS.13	25mm*20mm	13mm	6900	13800	
DN20	GDSIHCSST25030JS.20	25mm*20mm	20mm	3840	7680	
DN25	GDSIHCSST32030JS.13	32mm*26mm	13mm	4280	8560	
DN25	GDSIHCSST32030JS.20	32mm*26mm	20mm	2400	4800	

REMARKS:

①HT Insulation pipe: Means EPDM based insulation pipe,can resist temperature from - 50℃ ,up to 175 °C operating intermittent,UV resistance Surface treatment

②Jacketing: means the jacketing coated on the insulation pipe is with a super high density water proof polyolefin copolymer foil.have excellent performance of UV-resistance ,water proof and bird peck-Protective or mechanical destroy